



Call from the UK
0800 433 4833

Airstop Sealing Plaster

DESCRIPTION

Airstop Sealing Plaster is a tear-resistant adhesive patch with adhesive generously applied and is suitable for sealing holes in a variety of substrates, **indoors and out**. It is suitable for applying to substrates such as plywood, OSB and membranes. Its reinforced make-up makes it resistant to tearing.

BENEFITS/USAGE

- A quick seal for larger openings, e.g. blow-in openings

PREPARATION

Any surface being adhered to should be properly prepared and must be free from dust and grease and substrates must be dry.

APPLICATION

Remove backing and apply evenly over hole, ensuring adequate coverage. Adhesive is pressure sensitive so ensure adequate pressure is applied across entire surface to be sealed.

NOTE

Airstop Sealing Plaster functions as a seal and not as a mechanical fixing. The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore **this product is extremely resistant to ageing**. Please pay attention to our Guidelines for Installation!

PROPERTIES

Composition	Tear-resistant synthetic base with pure acrylate adhesive	
Roll Widths mm	180	200
Roll Length m	18	200
Pieces per roll	222	200
Carton/rolls	4	4
Thickness	0.3mm	
Temperature Resistance	-40°C to +100°C	
Working temperature	From -5°C	
Resistance to Ageing	30 years	
Storage	2 years, cool and dry	
Outdoor Exposure	Max. 1 month	
Colour	White with green Airstop imprint	

