



Call from the UK
0800 433 4833

Airstop Ultra Adhesive Tape

DESCRIPTION

Airstop Ultra Adhesive Tape is slightly expandable with adhesive generously applied. It is suitable for a variety of bonding applications and can also be used on problematic substrates such as PP foils outdoors.

BENEFITS/USAGE

- Adhesion of vapour retarders & barriers
- Joins of OSB & DWD panels, indoors & outdoors
- Joints & connections with wood, masonry and metal
- For adhesion to masonry use **Bubi LF Bonding Primer** if necessary
- Bonding to PP foils
- High proportion of adhesive
- Slightly expandable (necessary when there is movement in the construction component)
- Adapts to the texture of the surface, i.e. better adhesion on surface that are not smooth

PREPARATION

Any surface being adhered to should be properly prepared and must be free from dust and grease and substrates must be dry. For porous substrates such as XPS, concrete, masonry, etc., please use **Bubi LF Bonding Primer** where necessary. The greater the pressure applied, the better the performance of the adhesive tape.

NOTE

Airstop ULTRA Adhesive Tape functions as a seal and not as a mechanical fixing. The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore **this product is extremely resistant to ageing**. Please pay attention to our Guidelines for Installation!

PROPERTIES

Composition	PE base material with polyester fabric and pure acrylate adhesive		
Roll Widths mm	60 white	60 black	100 black
Roll Length m	40	40	40
Rolls/Carton	10	10	6
Temperature Resistance	-40°C to +100°C		
Working Temperature	From -5°C		
Resistance to Ageing	20 years		
Storage	2 years, cool and dry		
Colour	White transparent/Black		
UV-Resistance	Max. 12 months		
Weatherproof	Max. 12 months		
UV-Resistance	Max. 2 months		
Color	Transparent white with green AIRSTOP imprint		

