



Omega Sealing Tape

DESCRIPTION

Omega Sealing Tape is used in particular for seals at problematic joints between threshold and concrete. Due to its high flexibility the tape can be attached over mounting brackets without any extra work.

BENEFITS/USAGE

- Sealing of threshold joints (concrete)
- Very expandable
- Resistant to moisture

PREPARATION

For optimum adhesion, all surfaces should be properly prepared and must be free from dust and grease and substrates must be dry. Optimum adhesion to the substrate is achieved in combination with **Bubi LF Bonding Primer**. The greater the pressure applied, the better the performance of the adhesive tape.

APPLICATION

Apply off the roll or cut to desired length. Press firmly into position. For further information see our application guidelines.

NOTE

Omega Sealing Tape functions as a seal and not as a mechanical fixing. Please pay attention to our Guidelines for Installation!

PROPERTIES

Composition	Bitumen tape, adhesive on one side, very flexible		
Roll Width	100mm	150mm	200mm
Roll Length	10m	10m	10m
Carton Contents	10 rolls	6 rolls	5 rolls
Thickness	Approx. 1.5mm		
Temperature Resistance	-40°C to +100°C		
Working Temperature	From +5°C		
Resistance to Ageing	10 years		
Storage	Cool and dry, 1 year		
Colour	Black		
Expandability	Approx. 300%		
UV-Resistance	Max. 4 months		

