



#### ADVANTAGES

- a stronger primer coat
- forms an adhesive film, self-adhesive
- working temperature from -10° C ( air and material temperature )

## BUBI LF Bonding primer

BUBI LF Bonding Primer is a quality, solvent-free primer for preparation of the substrate to optimize the adhesive properties of acrylate, butyl and bitumen- rubber adhesive tapes. It can be used on all absorbent, mineral substrates e.g. concrete, cement plaster, cellular concrete, brickwork and sand-lime bricks that are finished flush. Application is also possible on polystyrene panels. BUBI LF Primer is self-adhesive and resistant against humidity and warm temperatures.

#### AVAILABLE IN THE FOLLOWING DIMENSIONS

Cartridge	Dosing bottle	Pot
Quantity	1 kg	5 kg

#### PRODUCT DATA

Composition	Water- based acrylate polymer dispersion
Film characteristic	elastic
Drying time	15 - 40 min
Working temperature	- 5 °C - + 35 °C
Coverage	10 m <sup>2</sup> / kg
Storability	12 months in closed can, dry, closed + 15 °C - + 25 °C , without sun, the product is not frost- resistant!

INFO :  
+43 6216 / 4108  
WWW.ISOCELL.COM

**ISOCELL**

## GUIDELINES FOR USE

### BUBI LF Bonding primer

Stir BUBI LF Bonding Primer well, then spread evenly using a roller or a brush (apply twice to porous surfaces) and allow to dry. Be sure to apply evenly!

Before applying the adhesive tape the Primer should be dried to transparency. Thick Primer can be thinned by adding water.

The substrate must be level, firm, dry and free from grease, oil and dust.



INFO :  
+43 6216 / 4108  
[WWW.ISOCELL.COM](http://WWW.ISOCELL.COM)

**ISOCELL**