



OMEGA N55 Adhesive

Solvent-free adhesive for wind and waterproof adhesion of acrylate or TPU-coated façades and underroof membranes, either to each other, or to connect with concrete, wood and metal.

FIELD OF APPLICATION

- Adhesion at overlaps and joins for OMEGA UDO-s 330 and OMEGA facade membranes

ADVANTAGES

- plasticizer-resistant
- resistant to oil, petrol, dilute acids and leach
- 1-component
- Adhesion on many substrates e.g. wood, concrete, metal

AVAILABLE IN THE FOLLOWING DIMENSIONS

Package / Can	2,0 kg	4,5 kg
---------------	--------	--------

PRODUKT DATA

Composition	nitrile rubber
Density	0,88 g/cm ³
Working temperature	0 °C - + 40 °C
Coverage	40 g/m
Skin formation time dry/wet	10 min / 4 min
Storage	12 months unopened, room temperature
Colour	yellowish

INFO :
+43 6216 / 4108
WWW.ISOCELL.COM

ISOCELL

GUIDELINES FOR USE OF OMEGA N55 Adhesive

Wet bonding: apply OMEGA N55 to one of the grease and dust-free surfaces. The sections can be joined during skin-forming time.

Priming: on difficult, porous or highly absorbent surfaces OMEGA N55 can also be used as a primer. For this purpose, apply a thin layer to the substrate — allow to air out for approx. 15 min. — then apply adhesive to the sheeting and apply pressure immediately.



INFO :
+43 6216 / 4108
WWW.ISOCELL.COM

ISOCELL