



P-Seal – Seal for construction elements

Used as seal for floor elements and ceiling panels as well as other applications with mounting strap for stapling or nailing.

FIELD OF APPLICATION

- Used as seal for floor elements and ceiling panels as well as other applications
- with mounting strap for stapling or nailing

ADVANTAGES

- does not absorb water; Water has no effect on the material
- high Temperature resistance
- chemically stable, uncomplicated in contact with other materials
- includes no diluents or additives, recyclable
- resistant to pressure loading

AVAILABLE IN THE FOLLOWING DIMENSIONS

Type	P 5,5 SK*	P 12	P 17	P 25
Roll width	9 mm	20 mm	27 mm	40 mm
Roll length	100 m	100 m	50 m	25 m
Thickness	5,5 mm	12 mm	17 mm	25 mm
Rolls / Carton	6	5	3	3

*self-adhesive

PRODUCT DATA

Composition	Hose with mounting strap out of EPDM cellular rubber
Temperature resistance	- 40 °C - + 150 °C
Sd - value	ca. 65 m
Sealing characteristic	To seal up at 50 Pascal air pressure difference; the opening breadth has to be at most 75% of the profile height
UV- resistance	fully and permanently
Resistance to aging	> 50 years
Colour	black
Storage	cool and dry

GUIDELINES FOR USE

P 5,5 includes a adhesive strip. But for proper fixation it was recommended to staple it also P 12, 17 and 25 are stapled to the underground through the mounting strap

