

# Uni Spray Bonding Primer

## DESCRIPTION

**Uni Spray Bonding Primer** is a quality synthetic rubber adhesive for preparation of the substrate to optimize the adhesive properties of acrylate, butyl and bitumen-rubber adhesive tapes. It can be used on all absorbent, mineral substrates, e.g. concrete, cement plaster, aerated concrete, brickwork and sand-lime bricks that are finished flush. Uni Spray Primer is self-adhesive and resistant against humidity and warm temperatures. Also suitable wood fibre board, rough timber etc. For XPS, EPS Please use our Bubi Lf Primer.

## BENEFITS/USAGE

- A stronger primer coat
- Self-adhesive working temperature from -5°C air and surface)
- Formulated specifically for the bonding of adhesive tapes
- Forms an adhesive film
- Fast Drying
- Fast Clean and Easy priming of rough and difficult profiles.
- Adjustable spray width tapes

## PREPARATION

As with any primer, preparation is key – ensure substrate to be primed is free from excessive moisture, dust and loose debris etc. In line with recommendations we always recommend the cleaning down and preparation of the surface to be primed. Clean off all dust – sweeping of the floor areas to be primed is generally sufficient.

## APPLICATION

Apply in an even and full coverage, thin applications works on most surfaces). On extremely porous surfaces you are better applying two coats instead of one thick one. 500ml can stretch some distance – expect 80–100 meters of a 50mm wide strip (270–330ft @ 2.5inches), Once dry to a clear tacky finish (usually within 10–20 minutes of application), the tape can be applied. Primer can be pre-applied prior to taping and left to dry overnight or as desired prior to taping as long as no dust is being generated within the environment.

## PROPERTIES

<b>Composition</b>	Synthetic rubber adhesive
<b>Cartridge</b>	500ml Spray Can or Large 22L Spray Canister
<b>Film Characteristic</b>	Elastic
<b>Working Temperature</b>	From -5°C (air and surface)/+35°C (primer)
<b>Flash-off time Summer / Winter</b>	10/20-40 Minutes Minutes (depending on the climate)
<b>Coverage</b>	50 meters 164ft at 100mm/4" wide, 100meters/328ft at 50mm/2" wide.
<b>Storability</b>	12 months when unopened; + 5 °C - + 25 °C , no direct UV-rays

**ADJUSTABLE SPRAY PRIMER**



**FORMULATED FOR BONDING WITH ADHESIVE TAPES**

## NOTE

The presence of humidity in the air/block-work may increase drying time. **Uni Primer** remains slightly tacky to the touch, even after drying – it is not only a primer but also an adhesive which helps to get the maximum adhesion of any tape applied to it. **Uni Primer** is self-adhesive and resistant against humidity and warm temperatures.



Austrian Innovation At Work In  
Ireland  
Ireland: +353 (0) 866 018 555  
+353 (0) 851 422 136  
[www.isocell.ie](http://www.isocell.ie)  
[info@isocell.ie](mailto:info@isocell.ie)



Austrian Innovation At Work In  
North America  
Canada FreePhone: 1-844-900-4288  
USA +1 646 8448 494  
[www.airstoptape.com](http://www.airstoptape.com)  
[info@airstoptape.com](mailto:info@airstoptape.com)



Austrian Innovation At Work In  
United Kingdom  
UK FreePhone: 0800 433 4833  
+44 (0) 20 8123 3305  
[www.isocelluk.co.uk](http://www.isocelluk.co.uk)  
[info@isocelluk.co.uk](mailto:info@isocelluk.co.uk)