


Declaration of Performance No. FA/2/1/1/1	Isocell GmbH A-5202 Neumarkt am Wallersee Bahnhofstrasse 36 Tel +43 (0)6216 41 08 –0 Fax +43 (0) 6216 79 79 office@isocell.at www.isocell.at
1. Unique identifying code of the product type:	Omega Fassadenbahn
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	Mentioned on the container or the printing
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	EN 13859-2 (11.2010): Flexible sheets for waterproofing. Part 2: Underlays for walls
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):	ISOCELL GmbH Bahnhofstraße 36 A- 5202 Neumarkt am Wallersee
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	./
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:	Kiwa MPA Bautest GmbH Niederlassung TBU Greven Institut für textile Bau- Umwelttechnik GmbH (PB Nr.1.1/16807/0007.0.1-2010) Klassifizierung nach DIN EN 13501-1; Prüfinstitut Hoch (KB-Hoch-100264) Bestimmung der Luftdichtheit nach DIN EN 13859-1/-2 und DIN EN 12114 (Forschungsinstitut für Wärmeschutz e.V. München; Bericht-Nr.: D3-11/10)
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	./

9. Declared performance		
Essential characteristics	Performance	Harmonised technical specification
Length: Width: Weight: Fire class: Resistance to water penetration: Maximum tensile force MD Maximum tensile force CD: Tear resistance MD: Tear resistance CD: Elongation MD: Elongation CD: Water vapour transmission properties: Change in % after artificial aging: Maximum tensile force MD: Maximum tensile force CD: Elongation MD: Elongation CD: Resistance to water penetration:	50 m 1,35m; 2,5 m 177 g/m ² B-s2,d0 0 ml (W2) 330 N/50 mm 308 N/50 mm 109 N 111 N 26% 31% sd 0,17 m (± 0,05m) Residual value 212 N/50 mm 186 N/50 mm 6% 7% 0 ml (W2)	EN 13859-2
<p>10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:</p> <div style="display: flex; justify-content: space-between; align-items: flex-end; margin-top: 20px;"> <div style="width: 45%;"> <p>Spitaler Anton (Managing Director)</p> <hr style="border: 0; border-top: 1px solid black;"/> <p>(Name and function)</p> </div> <div style="width: 45%; text-align: center;">  </div> </div> <div style="display: flex; justify-content: space-between; align-items: flex-end; margin-top: 10px;"> <div style="width: 45%;"> <p>Neumarkt a.W. 30.06.2013</p> <hr style="border: 0; border-top: 1px solid black;"/> <p>(Place and date of issue)</p> </div> <div style="width: 45%; text-align: center;"> <p>(Signature)</p> </div> </div>		