


<p><b>Declaration of Performance</b> No. DB 16/2/1/1</p>	<p><b>Isozell GmbH</b> A-5202 Neumarkt am Wallersee Bahnhofstrasse 36 Tel +43 (0)6216 41 08 –0 Fax +43 (0) 6216 79 79 office@isocell.at <span style="float: right;">www.isocell.at</span></p>
<p>1. Unique identifying code of the product type:</p>	<p>Omega Dampfbremse (Plus, SK, SK DUO)</p>
<p>2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)</p>	<p>Mentioned on the container or the printing</p>
<p>3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p>	<p>EN 13984 Flexible sheets for waterproofing - Plastic and rubber vapour control layers</p>
<p>4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):</p>	<p>ISOCELL GmbH Bahnhofstraße 36 A- 5202 Neumarkt am Wallersee</p>
<p>5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):</p>	<p>./.</p>
<p>6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:</p>	<p>System 3</p>
<p>7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:</p>	<p>TECHNICKY A SKUSOBNY USTAV STAVEBNY n.O. NB 1301  Hat die Bewertung und Überprüfung nach System 3 vorgenommen.</p>
<p>8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:</p>	<p>./.</p>

9. Declared performance		
Essential characteristics	Performance	Harmonised technical specification
Length:	50 m	EN 13984
Width:	1,5; 3,0 m	
Mass per unit area	140 ( ±12) g/m <sup>2</sup>	
Maximum tensile force MD:	255 N/50 mm (-55/+95)	
Maximum tensile force CD:	190 N/50 mm (-30/+75)	
Elongation MD:	55 % (-20/+40)	
Elongation CD:	65 % (-20/+40)	
Tear resistance MD:	195 N (-40/+105)	
Tear resistance CD:	255 N (-35/+70)	
Water vapour transmission properties:	10m (-4/+8)	
Reaction to fire:	E	
Watertightness:	W 1	
Change after artificial aging:		
Water vapour transmission properties:	pass	
<p>10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:</p>		
Spitaler Anton (Managing Director)		
(Name and function)		
Neumarkt a.W. 03.12.2014		
(Place and date of issue)	(Signature)	