



Uni Primer

DESCRIPTION

Uni Primer is a quality, solvent-based synthetic-resin primer for preparation of the substrate to optimize the adhesive properties of cold-setting adhesive tapes, cold self-adhesive roof underlays, etc. It can be used on all absorbent mineral substrates e.g. concrete, bricks, wood, etc.

Advantages compared with bitumen primer:

Temperature resistance up to 100°C and can also be used at -10°C. It penetrates 3mm into the surface and forms a firm bond between material and adhesive.

Quick drying: In summer approx. 15 mins.
Winter 30–45 mins.

Coverage: Approx. 0.3 l/m or approx. 1.0 l/100m
(applied approx. 3cm)

PROPERTIES

Working Temperature	From -10°C	
Packing	1 Liter	5 Liter
Carton	20 Cans	1 Can
Temperature Resistance	To +100°C	
Drying Time	Summer 10 minutes, Winter 30–45 minutes	
Storage	Approx. 12 months in closed can. NOTE: Take into consideration that it is highly inflammable	

BENEFITS/USAGE

- A stronger primer coat
- Resistant to +100°C
- Working temperature from -10°C
- Quick drying & economical in use

PREPARATION

The substrate must be smooth, firm, dry, free from grease, oil and dust.

APPLICATION

Apply **Uni Primer** evenly using a roller or a brush (spread on porous surfaces twice) and allow to dry.

NOTE

Protective gloves and goggles must be worn as protection against the solvent! Use only in ventilated places!

